

LOCK INTO THE ACSI ADVANTAGE



MORTISE KEY SWITCH
PUSHBUTTON SWITCH
EMERGENCY RELEASE
DOOR POSITION SWITCH
INDICATORS
AUDIBLE ALARM
KEYPADS

S E R I E S 1 3 0 0 D O O R C O N T R O L S C A T A L O G



SERIES 1300 DOOR CONTROLS

MORTISE KEYSWITCH*

ACSI Series 1310 Mortise Keyswitches are designed to control electric locks, electric strikes, electric exit devices, and a variety of other control applications. ACSI 1310 keyswitches allow keying the electrically controlled openings to facility master key systems. DPDT contacts.



Model	Description
1310-1	Keyswitch, single gang, wall mount
1310-2	Keyswitch, single gang, 2 indicators (Red and Green), wall mount
1310-3	Keyswitch, double gang, adjustable time delay (0-30 sec.), wall mount
1310-3-2	Keyswitch, double gang, adjustable time delay (0-30 sec.), 2 indicators (Red and Green), wall mount
1310-4	Keyswitch, narrow style, 1-3/4" frame mount
1310-4-2	Keyswitch, narrow style, 2 indicators (Red and Green), frame mount
1310-5	Keyswitch, double gang, audible alarm, wall mount
1310-5-2	Keyswitch, double gang, audible alarm, 2 indicators (Red and Green), wall mount

PUSHBUTTON SWITCH*

ACSI Series 1320 Pushbutton Switches provide a variety of functions for commercial and industrial door control applications. DPDT contacts.



Model	Description
1320-1	Pushbutton, single gang, wall mount
1320-2	Pushbutton, single gang, 1 indicator (Red or Green), wall mount
1320-3	Pushbutton, single gang, 2 indicators (Red and Green), wall mount
1320-4	Pushbutton, double gang, adjustable time delay (0-30 sec.), 1 indicator (Red or Green), wall mount
1320-5	Pushbutton, single gang, mushroom switch, wall mount**
1320-5-2	Pushbutton, single gang, mushroom switch, 2 indicators (Red and Green), wall mount**
1320-6	Pushbutton, narrow style, 1-3/4" frame mount
1320-6-2	Pushbutton, narrow style, 2 indicators (Red and Green), 1-3/4" frame mount

*When ordering Part No. 1310 or 1320, specify momentary or maintained action.
 **Contacts available in SPDT form only.

EMERGENCY RELEASE

Attractive and durable, ACSI 1330-2 Emergency Release provides manual emergency reporting. The 1330-2 is finished in blue enamel. Supplied with separate N.O. and N.C. contact outputs.

<u>Model</u>	<u>Description</u>
1330-2	Emergency Release



DOOR POSITION SENSORS

ACSI 1335 Door Position Sensors are used to confirm door position. Magnetic sensors mounted in the frame react to the proximity of a magnet mounted in the door. Pneumatic models also available for use in hazardous locations.

<u>Model</u>	<u>Description</u>
1335-1	D.P.S. Standard mortise, SPDT, N.O./N.C. contacts
1335-2	D.P.S. ANSI, SPDT, N.O./N.C. contacts
1335-3	D.P.S. Surface mount, SPDT, N.O./N.C. contacts
1335-4	D.P.S. Standard mortise, AIR, Three-way, N.O. ports
1335-5	D.P.S. ANSI, AIR, Three-way, N.O. ports



INDICATORS

ACSI 1340 Indicators provide visual or audible indication of system status.

<u>Model</u>	<u>Description</u>
1340-1	Indicator, single gang, round LED (Red or Green), wall mount
1340-2	Audible alarm, single gang, wall mount
1340-3	High security audible alarm, single gang, wall mount



DIGITAL KEYPADS

ACSI Digital Keypads offer proven reliability for commercial, industrial, and residential applications. The 1355 Keypads are designed to control any electric locking device.

Features

- Keypad programmable
- 10-30 VDC; 12-24VAC – auto adjusting (for all models except 1355-7)
- 120 user capability
- Over 1 million code combinations
- Adjustable relock delay (1-90 seconds)
- LED status indicators (for all models except 1355-4)
- Request to exit switch input
- Main Relay ON/OFF latching (toggle mode)
- Panic output (for all models except 1355-6 & 1355-7)
- Interface to alarm system
- On board SPDT 8 amp main relay
- Non-volatile memory remembers codes and instructions when power is removed

Model	Description
1355-1	Digital Indoor Keypad
1355-2	Weather Resistant Keypad
1355-3	Sealed Environmental Keypad <ul style="list-style-type: none"> • Weatherproof self-contained metal housing • Vandal resistant • Small design suitable for commercial, industrial, and residential applications
1355-4	Ruggedized Digital Keypad <ul style="list-style-type: none"> • Weatherproof self-contained metal housing • Vandal resistant • One piece housing suitable for wall, post, or gooseneck mounting • Internal audible multi-status indicator (sounder) • Available in white or black
1355-5	Mullion Digital Keypad <ul style="list-style-type: none"> • Weather resistant for outdoor, as well as indoor applications • Backlit hardened keys • Doorbell key w/associated relay output • Narrow style suitable for aluminum door frame mounting • Available in bronze or aluminum
1355-6	Indoor Backlit Keypad <ul style="list-style-type: none"> • Elegant design • Illuminated backlit hardened keys • Heavy traffic application • Flush mount design • Includes audible indicator (sounder)
1355-7	Harsh Environment Keypad <ul style="list-style-type: none"> • Vandal and weatherproof case construction • For indoor/outdoor applications • Attractive appearance • Touch sensitive flat key design won't wear out • Includes audible indicator (sounder) • 12/24 volts AC/DC – jumper selectable



1355-1



1355-2



1355-3



1355-4



1355-5



1355-6



1355-7

ELECTRIC SPECIFICATIONS

1310/1320 Switches:

- DPDT Contact Configuration
- Contacts Rated 1A @ 30VDC

Note: 1320-5 SPDT contact only.

1330-2 Emergency Release Switch:

- Separate N.O./N.C. Outputs
- Can be wired for SPDT Contact Configuration
- Contacts Rated 1A @ 30 VDC

1340-2 & 1340-3 Audible Alarm

- DC Voltage Range: 4V - 28V
- DC Current Range: 2mA - 14mA
- Frequency: 2900 Hz
- Sound Intensity: 64dB @ Min. V; 78dB @ Max. V

Red/Green LED Indicator Used with

1310/1320/1340 Controls:

- 24VDC, 20mA, 10mcd